



TF 9090 - Data Sheet

Description

TF 9090 is a tire designed for small tractors in soil tillage operations. The special tread design provides excellent steering performance on loose soil.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Small Tractor

Industrial: Trailer



SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
4.00 - 12	STANDARD	F2	60 A6	4	3.00 D	2.50 C	112	530	255	1573	TT	E4-106R-002181
4.00 - 12	STANDARD	F2	68 A6	6	3.00 D	2.50 C	112	530	255	1573	TT	E4-106R-002182
5.00 - 15	STANDARD	F2	73 A6	4	4.00 E	3.00 D ; 4 J ; 4½ J	140	655	307	1951	TT	E4-106R-001952
5.00 - 15	STANDARD	F2	82 A6	6	4.00 E	3.00 D ; 4 J ; 4½ J	140	655	307	1951	TT	
10.00 - 16	SPECIAL	F2	115 A6	8	W 8	W 8 L	275	900	409	2714	TT	
10.00 - 16	SPECIAL	F2	119 A6	10	W 8	W 8 L	275	900	409	2714	TT	E11-106R-004418
10.00 - 16	STANDARD	F2	115 A6	8	W 8	W 8 L	275	900	409	2714	TT	E4-106R-002672
10.00 - 16	STANDARD	F2	119 A6	10	W 8	W 8 L	275	900	409	2714	TT	E4-106R-002671
11.00 - 16	SPECIAL	F2	118 A6	8	W 10 L	W 8 ; W 8 L	320	970	448	2890	TT	E11-106R-004316
11.00 - 16	STANDARD	F2	118 A6	8	W 10 L	W 8 ; W 8 L	320	970	448	2890	TL	E4-106R-002673
11.00 - 16	STANDARD	F2	118 A6	8	W 10 L	W 8 ; W 8 L	320	970	448	2890	TT	E4-106R-002673
4.00 - 16	STANDARD	F2	69 A6	4	3.00 D		112	630	301	1877	TT	E4-106R-002183
5.50 - 16	STANDARD	F2	86 A6	6	4.00 E	3.50 D ; 4.50 E	150	710	332	2116	TT	E4-106R-001955
6.00 - 16	SPECIAL	F2	88 A6	6	4.50 E	4.00 E ; 5 K ; 5.00 F	170	735	346	2190	TT	E11-106R-004410
6.00 - 16	SPECIAL	F2	94 A6	8	4.50 E	4.00 E ; 5 K ; 5.00 F	170	735	346	2190	TT	E11-106R-004415
6.00 - 16	STANDARD	F2	88 A6	6	4.50 E	4.00 E ; 5 K ; 5.00 F	170	735	346	2190	TT	E4-106R-001959
6.00 - 16	STANDARD	F2	94 A6	8	4.50 E	4.00 E ; 5 K ; 5.00 F	170	735	346	2190	TT	E4-106R-001961
6.50 - 16	STANDARD	F2	91 A6	6	4.50 E	4.00 E ; 5 K ; 5.00 F ; 5.50 F	180	765	359	2280	TT	E4-106R-001960
6.50 - 16	STANDARD	F2	98 A6	8	4.50 E	4.00 E ; 5 K ; 5.00 F ; 5.50 F	180	765	359	2280	TT	E4-106R-001962
7.50 - 16	SPECIAL	F2	98 A6	6	5.50 F	5.00 F ; 5 K ; 6.00 F	207	810	379	2414	TT	E11-106R-004412
7.50 - 16	SPECIAL	F2	103 A6	8	5.50 F	5.00 F ; 5 K ; 6.00 F	207	810	379	2414	TT	E11-106R-004413
7.50 - 16	STANDARD	F2	98 A6	6	5.50 F	5.00 F ; 5 K ; 6.00 F	207	810	379	2414	TT	E4-106R-002634
7.50 - 16	STANDARD	F2	103 A6	8	5.50 F	5.00 F ; 5 K ; 6.00 F	207	810	379	2414	TT	E4-106R-002709
7.50 - 16	STANDARD	F2	109 A6	10	5.50 F	5.00 F ; 5 K ; 6.00 F	207	810	379	2414	TT	E4-106R-002708
9.00 - 16	SPECIAL	F2	116 A6	10	W 8	6.00 F ; W 7 ; W 8 L	257	855	398	2548	TT	E11-106R-004114
9.00 - 16	STANDARD	F2	111 A6	8	W 8	6.00 F ; W 7 ; W 8 L	257	855	398	2548	TT	E4-106R-002668
9.00 - 16	STANDARD	F2	116 A6	10	W 8	6.00 F ; W 7 ; W 8 L	257	855	398	2548	TT	E4-106R-002669
7.50 - 18	SPECIAL	F2	101 A6	6	5.50 F		207	860	404	2562	TT	
7.50 - 18	SPECIAL	F2	106 A6	8	5.50 F		207	860	404	2562	TT	E11-106R-004318
7.50 - 18	STANDARD	F2	113 A6	10	5.50 F		207	860	404	2562	TT	E11-106R-004654
7.50 - 18	STANDARD	F2	101 A6	6	5.50 F		207	860	404	2562	TT	E11-106R-004317
7.50 - 18	STANDARD	F2	106 A6	8	5.50 F		207	860	404	2562	TT	E4-106R-002645
4.00 - 19	STANDARD	F2	72 A6	4	3.00 D		115	715	343	2145	TT	E11-106R-003355
6.00 - 19	STANDARD	F2	93 A6	6	4.50 E	4.00 E ; 5.00 F	167	815	386	2445	TT	E11-106R-003472
7.50 - 20	SPECIAL	F2	103 A6	6	5.50 F	5.00 F	205	915	431	2725	TT	
7.50 - 20	SPECIAL	F2	109 A6	8	5.50 F	5.00 F	205	915	431	2725	TT	
7.50 - 20	STANDARD	F2	103 A6	6	5.50 F	5.00 F	205	915	431	2725	TT	E4-106R-002635
7.50 - 20	STANDARD	F2	109 A6	8	5.50 F	5.00 F	205	915	431	2725	TT	E4-106R-002710

Printed on 26/04/2024 00:10

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for

undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..