



TR 138 - Data Sheet



Description

TR 138 has been specially designed for telehandlers and backhoe loaders in agriculture. It is best suitable for soil tillage and spraying applications. Excellent traction on soft soil, best self-cleaning properties and stability are key features which make the TR 138 tire the ideal partner even with difficult ground conditions.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Backhoe Loader • Telehandler

| SIZE | Version | USACode | LI/SS | PR | RIM REC | RIM ALT | SW | OD | SLR | RC | Type | ECE |
|------------|----------|----------|--------|----|---------|---------|------|------|------|-----|------|-----------------|
| 17.5L - 24 | STANDARD | 94061877 | 151 A8 | 12 | DW 15L | DW 14L | 17.7 | 50.8 | 22.7 | 151 | TL | E11-106R-005232 |

Printed on 28/04/2024 22:37

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..