

## TR 171 - Technical Specifications



### Description

TR 171 is a deep tread tire suitable for tractors in soil tillage operations. Thanks to its outstanding self-cleaning properties, it is ideal for wet and moist soil. Designed with a special compound, TR 171 provides excellent traction and extraordinary durability also in the harshest operating conditions.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TT
Tyre Size	13.6 - 26
LI/SS	126 A6

## Dimensions International Standard

Ply Rating	8
TKPH	1
Section Width (mm)	340
Overall Diameter (mm)	1270
Static Loaded Radius (mm)	587
Rolling Circumference (mm)	3835
Rim Rec	W 12
Rim Alt	W 11
ECE	E11-106R-004481
TRA Code	R1W+

## Load capacity (Kg)

km/h / bar	2.20
30	1700

Printed on 17/04/2024 03:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..