

## TR 270 - Technical Specifications



### Description

TR 270 is a tractor tire suitable for soil tillage applications. It is specially designed for providing maximum performance on wet and moist soil. In these soil conditions, a tire is required to offer superior grip and enhanced self-cleaning features. TR 270 perfectly meets all these characteristics.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Tractor

Version	STANDARD
Type	TT
Tyre Size	20.8 - 38
LI/SS	148 A8

## Dimensions US Standard

Usa code	94026531
Ply Rating	10
Section Width (inch)	20.9
Overall Diameter (inch)	73.8
Static Loaded Radius (inch)	33.9
Rolling Circumference (inch)	224.2
Rim Rec	W 18 A ; W 18 L
Rim Alt	DD 18 ; DW 18 A
ECE	E11-106R-004512
TRA Code	R2

## Load capacity (lbs)

mph / psi	22
25	6950

Printed on 27/04/2024 11:35

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..