

## TR 315 - Technical Specifications



### Description

TR 315 is suitable for lawn and garden, soil tillage and municipalities operations. It is ideal with implement machinery, trenchers and orchard harvesters. The TR 315 tire has a large contact area which provides excellent grip, great self-cleaning properties and outstanding stability in any condition.

### UM

International Standard

### Construction

 BIAS

### Machinery

Agriculture: Implement Machinery • Orchard Harvester •  
Trencher

|           |                |
|-----------|----------------|
| Version   | STANDARD       |
| Type      | TL             |
| Tyre Size | 23 X 8.50 - 12 |

## Dimensions International Standard

|                            |                                      |
|----------------------------|--------------------------------------|
| Ply Rating                 | 4                                    |
| Section Width (mm)         | 205                                  |
| Overall Diameter (mm)      | 575                                  |
| Static Loaded Radius (mm)  | 258                                  |
| Rolling Circumference (mm) | 1668                                 |
| Rim Rec                    | 7 JA ; 7.00 I - 55 ; I - 70 ; I - 90 |
| ECE                        | E11-106R-004518                      |

## Load capacity (Kg)

| km/h / bar | 1.50 |
|------------|------|
| 15         | 500  |

Printed on 23/04/2024 17:31

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..