

TR 318 - Technical Specifications



Description

TR 318 is specifically designed for sprayers and implement machinery. Its dual-angled lugs provide excellent traction and outstanding driving comfort. TR 318 also features extraordinary self-cleaning properties.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Sprayer

| | |
|-----------|-----------------|
| Version | STANDARD |
| Type | TT |
| Tyre Size | 26 X 10.00 - 12 |
| LI/SS | 107 A3 |

Dimensions International Standard

| | |
|-----------------------|-----------------|
| Ply Rating | 8 |
| Section Width (mm) | 265 |
| Overall Diameter (mm) | 675 |
| Rim Rec | 8.5 |
| ECE | E11-106R-004522 |

Load capacity (Kg)

| km/h / bar | 3.70 |
|------------|------|
| 15 | 975 |

Printed on 27/04/2024 11:42

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..