

TR 319 - Technical Specifications



Description

TR 319 is a tire for implement machinery, orchard harvesters and trenchers in lawn and garden, municipality and soil tillage applications. Featuring a large contact area providing best traction, TR 319 is very suitable for applications on wet surfaces, where stability and self-cleaning properties are required.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Implement Machinery • Orchard Harvester • Trencher

Version	STANDARD
Type	TL
Tyre Size	26 X 12.00 - 12
LI/SS	116 A3

Dimensions US Standard

Usa code	94043637
Ply Rating	8
Section Width (inch)	12.5
Overall Diameter (inch)	25.2
Static Loaded Radius (inch)	11.4
Rolling Circumference (inch)	75.1
Rim Rec	10.50 AT
Rim Alt	8.0 AT ; 8.5 AT ; 9.0 AT
ECE	E11-106R-003560

Load capacity (lbs)

mph / psi	44
10	2760

Printed on 25/04/2024 05:55

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..