

## TR 390 - Technical Specifications



### Description

TR 390 is an agro-industrial tire suitable for sugar cane trailers and compactors. TR 390 features high load capacity and increased durability. Its "dual bead HD" version is particularly suitable for industrial tractors and transport operations using trailers, whereas its "dual bead HD special" version is ideal for heavy-duty service.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Trailer

Industrial: Compactor

Version	DUAL BEAD HD
Type	TL
Tyre Size	23.1 - 26
LI/SS	157 A8

## Dimensions US Standard

Usa code	94030675
Ply Rating	18
Section Width (inch)	23.4
Overall Diameter (inch)	61.4
Static Loaded Radius (inch)	27.2
Rolling Circumference (inch)	178.9
Rim Rec	DW 20 B
ECE	E11-106R-004607
TRA Code	R3

## Load capacity (lbs)

mph / psi	38
25	9090

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 21/05/2025 21:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..