

TR 391 - Technical Specifications



Description

TR 391 is an agro-industrial tire suitable for transport and compacting operations with sugar cane trailers and compactors. TR 391 features high load capacity and a longer service life.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Trailer
Industrial: Compactor

| | |
|-----------|-----------|
| Version | STANDARD |
| Type | TL |
| Tyre Size | 14.9 - 24 |
| LI/SS | 128 A6 |

Dimensions International Standard

| | |
|----------------------------|-------------------------|
| Ply Rating | 8 |
| Section Width (mm) | 405 |
| Overall Diameter (mm) | 1270 |
| Static Loaded Radius (mm) | 574 |
| Rolling Circumference (mm) | 3805 |
| SRI (mm) | 600 |
| Rim Rec | DW 13 |
| Rim Alt | DW 11 ; DW 12 ; DW 13 L |
| ECE | E11-106R-003365 |
| TRA Code | R3 |

Load capacity (Kg)

| km/h / bar | 1.80 |
|------------|------|
| 30 | 1800 |

Printed on 25/04/2024 02:51

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..