

TR 393 (B) - Data Sheet



Description

TR 393 (B) has been specially designed for seeders, spreaders and implement machinery on and off the road. The special tread design provides best flotation and selfcleaning properties in addition to a long service life. Thanks to its large contact area, TR 393 ensures excellent traction and minimizes soil compaction.

UM

International Standard

Construction

🕉 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Spreader

| SIZE | Version | TRA Code | LI/SS | PR | RIM REC | RIM ALT | SW | OD | Туре | ECE |
|-----------------|-------------------|----------|-------|----|---------|---------|-----|-----|------|-----------------|
| 31 X 13.50 - 15 | STUBBLE RESISTANT | R3 | 124 B | 12 | 10 LB | | 350 | 777 | TL | E11-106R-008131 |

Printed on 17/05/2024 15:33

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..