



# TR 463 - Technical Specifications

## Description

TR 463 has been specially designed for backhoe loaders and industrial tractors. Made of a superior tread compound and featuring a strong nylon casing, this tire stands for best results in industrial and OTR applications, and on construction sites. TR 463 provides excellent traction for drive wheels.

## UM

International Standard

## Construction

 BIAS

## Machinery

Industrial: Backhoe Loader • Industrial Tractor



Version	INDUSTRIAL
Type	TL
Tyre Size	16.9 - 24
LI/SS	149 A8

## Dimensions International Standard

Ply Rating	12
Section Width (mm)	445
Overall Diameter (mm)	1300
Static Loaded Radius (mm)	584
Rolling Circumference (mm)	3877
Rim Rec	DW 15 L
Rim Alt	DW 14 L
TRA Code	R4

## Load capacity (Kg)

km/h / bar	2.60
40	3250

Printed on 25/04/2024 10:34

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..