

TRAC FARM PLUS - Technical Specifications



Description

TRAC FARM PLUS is a rear tractor tire specifically designed for soil tillage and haulage applications. The tire features a deeper tread with dual angle lugs to ensure both excellent traction and a comfortable ride on the road. The special tread design provides more contact for better stability and great self-cleaning properties. TRAC FARM PLUS ensures a longer tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TT
Tyre Size	16.9 - 30
LI/SS	144 A6

Dimensions International Standard

Ply Rating	12
Section Width (mm)	440
Overall Diameter (mm)	1475
Static Loaded Radius (mm)	679
Rolling Circumference (mm)	4466
Rim Rec	W 15 L
Rim Alt	W 14 L
ECE	E11-106R-004529
TRA Code	R1

Load capacity (Kg)

km/h / bar	2.40
30	2800

Printed on 27/04/2024 12:18

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..