



TRAC FARM PLUS - Data Sheet



Description

TRAC FARM PLUS is a rear tractor tire specifically designed for soil tillage and haulage applications. The tire features a deeper tread with dual angle lugs to ensure both excellent traction and a comfortable ride on the road. The special tread design provides more contact for better stability and great self-cleaning properties. TRAC FARM PLUS ensures a longer tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
12.4 - 28	STANDARD	R1	125 A6	12	W 11	W 9 ; W 10	320	1295	603	3899	TT	E11-106R-004526
13.6 - 28	STANDARD	R1	128 A6	12	W 12	W 11	365	1345	621	4088	TT	E11-106R-004527
14.9 - 28	STANDARD	R1	134 A6	12	W 13	W 12 ; W 11	390	1380	642	4179	TT	E11-106R-006811
16.9 - 28	STANDARD	R1	143 A6	12	W 15 L	W 14 L	440	1435	660	4298	TT	E11-106R-003627
16.9 - 30	STANDARD	R1	144 A6	12	W 15 L	W 14 L	440	1475	679	4466	TT	E11-106R-004529

Printed on 27/04/2024 05:01

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..