

TRAC GRADER + - Technical Specifications



Description

TRAC GRADER + (G-2) is a bias-ply tire for graders. It is an excellent choice for the budget-minded customers. The durable casing is designed to last. The self-cleaning tread design shows open lug-to-void-ratio which provides best traction in all conditions. Its special version is made of a special cut-and-chip-resistant compound.

UM

International Standard

Construction

 BIAS

Machinery

OTR: Grader

Version	SPECIAL
Type	TL
Tyre Size	14.00 - 24

Dimensions International Standard

Ply Rating	12
Overall Width (mm)	364
Overall Diameter (mm)	1348
Static Loaded Radius (mm)	598
Rolling Circumference (mm)	3990
Rim Rec	8.00 TG SDC
Rim Alt	9.00/1.5 (DC) ; 10.00/VA SDC; 10.00 WA SDC
TRA Code	G2

Load capacity (Kg)

km/h / bar	2.50
40	3075

Printed on 21/02/2024 05:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..