

XL GRIP (ADT) - Data Sheet



Description

XL GRIP (ADT) is a bias-ply tire for Articulated dump trucks designed to minimize cuts and punctures in severe conditions where exceptional traction is required. These features result in an extended tire life.

UM

International Standard

Construction

✚ BIAS

Machinery

OTR: Articulated Dump Truck (ADT)

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
26.5 - 25	STANDARD	E3	32	22.00/3.0		680	1740	796	5150	TL	36
26.5 - 25	STANDARD	E3	28	22.00/3.0		680	1740	796	5150	TL	36
29.5 - 25	STANDARD	E3	28	25.00/3.5		760	1860	849	5544	TL	39
29.5 - 25	STANDARD	E3	32	25.00/3.5		760	1860	849	5544	TL	39

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 09/05/2025 10:13

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..