



XL GRIP (G3) - Data Sheet



Description

XL GRIP (G-3) is a bias-ply tire for graders designed to minimize cuts and punctures in heavy-duty grading environments where exceptional traction is required.

UM

US Standard

Construction

 BIAS

Machinery

OTR: Grader

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
13.00 - 24	STANDARD	94047796	G3	16	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	13.8	51	23.7	152.4	TL
13.00 - 24	STANDARD	94062928	G3	16	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	13.8	51	23.7	152.4	TT
14.00 - 24	STANDARD	94031436	G3	16	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	14.4	53	24.3	157.6	TL
14.00 - 24	STANDARD	94062959	G3	16	8.00 TG SDC	9.00/1.5 (DC) ; 10.00/VA SDC	14.4	53	24.3	157.6	TT
16.00 - 24 (-)	STANDARD	94044276	G3	16	10.00 VA SDC	-	17	57.1	25.7	168.9	TL
18.00 - 25	STANDARD	94061839	G3	32	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TL
18.00 - 25	STANDARD	94061846	G3	40	13.00/2.5	15.00/2.5	20.1	63.6	29.1	188.2	TL

Printed on 23/04/2024 16:47

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..