



XL GRIP (T) - Data Sheet



Description

XL GRIP (E-3) best suits on/off trucks carrying heavy loads in mining applications. Its tread compound is designed to minimize cuts and punctures on harshest ground conditions. XL GRIP (E-3) offers exceptional traction and provides an extended tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

OTR: On/Off Truck

SIZE	Version	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type
8.25 - 16	STANDARD	16	6.50 H	6.00 G	238	870	0	0	TT
10.00 - 20	STANDARD	18	7.5	7.0	285	1075	505	3257	TT
11.00 - 20	STANDARD	18	8.0	7.5	297	1115	529	3368	TT
12.00 - 20	STANDARD	18	8.5	8.0	320	1155	545	3465	TT
12.00 - 20	STANDARD	20	8.5	8.0	320	1155	545	3465	TT
12.00 - 20	STANDARD	24	8.5	8.0	320	1155	545	3465	TT
12.00 - 24	STANDARD	20	8.5	8.0	320	1250	585	3710	TT
12.00 - 24	STANDARD	20	8.5	8.0	320	1250	585	3710	TL
12.00 - 24	STANDARD	24	8.5	8.0	320	1250	585	3710	TT

Printed on 20/04/2024 13:59

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..