



## AGRIMAX RT 955 - Data Sheet



### Description

AGRIMAX RT 955 is a BKT radial tire for row crop applications, while some sizes are also suitable for spraying and vineyards. The special tread design with a rounded shoulder provides excellent traction performance, stability and self-cleaning properties. Thanks to its strong casing, AGRIMAX RT 955 has a high load capacity.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Sprayer • Vineyard Harvester

SIZE	Version	USACode	TRA Code	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
<b>210/90 R 24 (8.3 R 24)</b>	STANDARD	94042531	R1	107 A8/B	W 7	W 6	8.4	39.8	18.2	119.2	TL	E4-106R-001818
<b>210/95 R 28 (8.3 R 28)</b>	STANDARD	94042548	R1	116 A8/B	W 7	W 6	8.4	43.7	20.2	132.4	TL	E4-106R-001819
<b>230/95 R 32 (9.5 R 32)</b>	STANDARD	94026678	R1	128 A8/B	W 7	W 8	9	49.3	23	150	TL	E4-106R-000764
<b>270/95 R 36 (11.2 R 36)</b>	STANDARD	94027484	R1	139 A8/B	W 9	W 8 ; W 10	10.8	56.2	26.2	170.7	TL	E4-106R-000659
<b>230/95 R 42 (9.5 R 42)</b>	STANDARD	94028610	R1	133 A8/B	W 7	W 8	9	59.3	28.1	180.9	TL	E4-106R-000772
<b>210/95 R 44 (8.3 R 44)</b>	STANDARD	94042760	R1	120 A8/B	W 7	W 6	8.4	59.8	28.4	183.2	TL	E4-106R-000771
<b>230/95 R 48 (9.5 R 48)</b>	STANDARD	94052837	R1	136D/139A8	W 7	W 8	9	65.2	31.2	200.2	TL	E11-106R-004067

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/01/2025 20:17

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..