



AS 2001 - Data Sheet



Description

AS 2001 is a bias cross-ply tire which best suits tractors in soil tillage operations. Its design provides excellent traction and self-cleaning properties. AS 2001 is made of a special cut-and-chip resistant compound that also ensures great load capacity.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Tractor

SIZE	Version	TRA Code	LI/SS	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
18.4 - 26	STANDARD	R1	146 A6	12	W 16 L	W 15 L	467	1475	650	4250	675	TT	E11-106R-003507
16.9 - 28	STANDARD	R1	135 A6	8	W 15 L	W 14 L	429	1420	651	4319	675	TT	E11-106R-003508
16.9 - 28	STANDARD	R1	143 A6	12	W 15 L	W 14 L	429	1420	651	4319	675	TT	E4-106R-002045
16.9 - 28	STANDARD	R1	143 A6	12	W 15 L	W 14 L	429	1420	651	4319	675	TL	E4-106R-002045

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/01/2025 21:30

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..