

## EARTHMAX SR 34 - Data Sheet



### Description

ARTHMAX SR 34 is an All Steel radial tyre specially engineered and designed for rigid dump trucks working in several operations like mining, quarry, logging and haulage. The non-directional block tread pattern provides excellent traction and stability on any type of terrain. EARTHMAX SR 34 is ideal for handling heavy loads. The strong All Steel casing features excellent wear and resistance to any snag and punctures. Its reinforced bead and the shoulder design contribute to an extended tire life-cycle even under the most heavy-duty service conditions.

### UM

International Standard

### Construction

 RADIAL

### Machinery

OTR: Rigid Dump Truck

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TKPH
16.00 R 25	CUT RESISTANT COMPOUND	E3+	***	183 B	11.25/2.0		440	1508	693	4575	TL	36	190
16.00 R 25	CUT RESISTANT COMPOUND	E3+	**	177 B	11.25/2.0		440	1508	693	4575	TL	36	190
16.00 R 25	ULTRA CUT RESISTANT COMPOUND	E3+	***	183 B	11.25/2.0		440	1508	693	4575	TL	36	

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/01/2025 20:46

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..