

## FL 630 SUPER - Technical Specifications



### Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Spreader • Tanker • Trailer

Version	STANDARD
Type	TL
Tyre Size	750/60 R 26.5
LI/SS	180 D

Dimensions US Standard

Usa code	94042135
Section Width (inch)	29.7
Overall Diameter (inch)	62
Static Loaded Radius (inch)	27.3
Rolling Circumference (inch)	189
Rim Rec	AG 24.00
ECE	E4-106R-001427

Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	5160	5960	6770	8210	9500	10950	12400	13360	14810	16090
40	5640	6530	7410	8990	10410	11990	13580	14640	16230	17640
30	6830	7900	8970	10890	12600	14520	16430	17710	19640	21340
25	7680	8880	10070	12230	14150	16310	18470	19920	22070	23980
15	8920	10320	11710	14220	16450	18960	21460	23140	25640	27860
5	10160	11750	13340	16190	18740	21590	24450	26350	29210	31740

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/10/2025 12:10 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..