

## FL 635 - Technical Specifications

### Description

FL 635 is a radial flotation tire suitable for both road and field usage. The special block pattern has been designed for hay baler applications. FL 635 ensures a great pressure distribution on the ground across the footprint and drastically reduces soil compaction to preserve the value of the crops. The tire ensures great self-cleaning properties, durability and traction along with excellent speed features.



### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Baler

Version	STANDARD
Type	TL
Tyre Size	650/55 R 22.5
LI/SS	167 D

## Dimensions US Standard

Usa code	94043521
Section Width (inch)	25.4
Overall Diameter (inch)	50.7
Static Loaded Radius (inch)	22.4
Rolling Circumference (inch)	153.6
Rim Rec	AG 20.00
ECE	E4-106R-000803

## Load capacity (lbs)

mph / psi	12	15	17	23	29	35	41	46	52	58
45	3510	4000	4490	5580	6350	7330	8310	9080	9950	10930
40	3850	4390	4930	6130	6980	8060	9140	9980	10930	12010
30	4660	5310	5960	7420	8440	9740	11060	12070	13240	14540
25	5240	5970	6710	8340	9490	10960	12430	13570	14880	16350
15	6080	6940	7790	9690	11020	12730	14440	15770	17280	18990
5	6920	7900	8870	11030	12540	14490	16450	17960	19690	21630

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/09/2024 07:02

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..