



## FL 635 - Data Sheet

### Description

FL 635 is a radial flotation tire suitable for both road and field usage. The special block pattern has been designed for hay baler applications. FL 635 ensures a great pressure distribution on the ground across the footprint and drastically reduces soil compaction to preserve the value of the crops. The tire ensures great self-cleaning properties, durability and traction along with excellent speed features.



### UM

US Standard

### Construction

 RADIAL

### Machinery

Agriculture: Baler

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
500/45 R 22.5	STANDARD	94075607	136 D	AG 16.00		19.3	40.2	18.1	121.5	TL	E11-106R-0010082
620/40 R 22.5	STANDARD	94048038	154 D	AG 20.00		24.6	42	18.5	127.9	TL	E4-106R-002399
650/55 R 22.5	STANDARD	94043521	167 D	AG 20.00		25.4	50.7	22.4	153.6	TL	E4-106R-000803
710/40 R 22.5	STANDARD	94053285	161 D	AG 24.00		28.6	44.9	20.1	136.5	TL	E11-106R-003014
750/45 R 22.5	STANDARD	94048786	168 D	AG 24.00		29.7	49.1	21.9	150	TL	E4-106R-002653

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 19/09/2024 07:23

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..