

FLOTATION 648 - Technical Specifications



Description

FLOTATION 648 is particularly suitable for field and road transport as well as for spreading operations. Some sizes are designed for hay harvesters/balers. The special tread design allows for carrying very heavy loads at low pressure, guaranteeing at the same time reduced soil compaction and preventing damage to crops.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Hay Harvester • Spreader

Version	HD
Type	TL
Tyre Size	650/65 - 30.5
LI/SS DRIVE WHEEL	169 A8/165 B
LI/SS FREE ROLLING	181 A8/178 B

Dimensions US Standard

Usa code	94030279
Ply Rating	18
Section Width (inch)	26.4
Overall Diameter (inch)	65.4
Static Loaded Radius (inch)	28
Rolling Circumference (inch)	194.3
Rim Rec	AG 20.00
ECE	E11-106R-004563

Load capacity (lbs)

mph / psi	33	35	36
5 FR	24240	24860	25460
10 FR	21810	22380	22920
20 FR	19400	19880	20370
25 FR	17320	17760	18190
30 FR	15590	15980	16530
5 DW	17050	17480	17900
10 DW	15340	15740	16110
20 DW	13650	13990	14320
25 DW	12180	12490	12790
30 DW	10970	11240	11350

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/9/2025 2:06 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..