



LG SMOOTH - Data Sheet

Description

LG SMOOTH is a lawn and garden tire suitable for mowers. While the tire is gentle on the ground, the enhanced design ensures increased durability and eases handling. LG SMOOTH is available in an "aramid-belted" version for users who need strengthened puncture resistance.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Mower • Small Tractor



SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
16 X 6.50 - 8	ARAMID BELTED	10	5.375 - 55 ; - 70 ; - 90		160	400			TL	
18 X 10.50 - 10	STANDARD	2	8.5 - 55 ; - 70 ; - 90	8½ JA	254	460	207	1334	TL	E11-106R-005203
20 X 10.00 - 10	ARAMID BELTED	6	8.00 - 55	7.00 - 55 ; - 70 ; - 90	245	500	223	1450	TL	E11-106R-005220
20 X 10.00 - 10	STANDARD	2	8.00 - 55	7.00 - 55 ; - 70 ; - 90	245	500	223	1450	TL	E11-106R-005201
20 X 10.00 - 10	STANDARD	4	8.00 - 55	7.00 - 55 ; - 70 ; - 90	245	500	223	1450	TL	E11-106R-003470
20 X 10.00 - 10	STANDARD	6	8.00 - 55	7.00 - 55 ; - 70 ; - 90	245	500	223	1450	TL	E11-106R-005202

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 15/10/2024 02:15

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..