



LOADER PLUS - Data Sheet

Description

LOADER PLUS (L-3) is a bias-ply tire specially designed for loaders. The tread compound provides cut-and-chip-resistant properties and suites best for loading and dozing operations.



UM

US Standard

Construction

 BIAS

Machinery

Industrial: Dozer • Loader

OTR: Dozer • Loader

SIZE	Version	USACode	TRA Code	PR	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
14.00 - 25	STANDARD	94064915	L3	20	10.00/1.5		14.8	53.9	24.8	159.4	TT	33
17.5 - 25	DUAL BEAD	94064953	L3	20	14.00/1.5		17.3	53	24.5	156.7	TT	33
17.5 - 25	STANDARD	94064939	L3	16	14.00/1.5		17.3	53	24.5	156.7	TT	33
17.5 - 25	STANDARD	94064946	L3	16	14.00/1.5		17.3	53	24.5	156.7	TL	33
20.5 - 25	STANDARD	94064984	L3	20	17.00/2.0		21.3	58.7	27	173.6	TT	37
20.5 - 25	STANDARD	94064991	L3	20	17.00/2.0		21.3	58.7	27	173.6	TL	37
20.5 - 25	STANDARD	94064960	L3	16	17.00/2.0		21.3	58.7	27	173.6	TT	37
20.5 - 25	STANDARD	94064977	L3	16	17.00/2.0		21.3	58.7	27	173.6	TL	37
23.5 - 25	STANDARD	94065042	L3	24	19.50/2.5		24	64.6	29.5	191.1	TL	41
23.5 - 25	STANDARD	94065004	L3	16	19.50/2.5		24	64.6	29.5	191.1	TT	41
23.5 - 25	STANDARD	94065011	L3	16	19.50/2.5		24	64.6	29.5	191.1	TL	41
23.5 - 25	STANDARD	94065028	L3	20	19.50/2.5		24	64.6	29.5	191.1	TT	41
23.5 - 25	STANDARD	94065035	L3	20	19.50/2.5		24	64.6	29.5	191.1	TL	41
26.5 - 25	STANDARD	94065066	L3	32	22.00/3.0		26.8	68.5	31.3	202.8	TL	46
26.5 - 25	STANDARD	94065059	L3	28	22.00/3.0		26.8	68.5	31.3	202.8	TL	46
29.5 - 25	STANDARD	94065073	L3	28	25.00/3.5		29.9	73.2	33.4	218.3	TL	49
29.5 - 25	STANDARD	94065080	L3	32	25.00/3.5		29.9	73.2	33.4	218.3	TL	49

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/9/2025 7:20 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..