

RIB 774 (A) - Technical Specifications



Description

RIB 774 (A) is a low-section implement tire offering high load capacity and a long tire life-cycle. It is suitable for hay harvesting and transport applications with balers and trailers.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Hay Harvester • Trailer

Version	ARAMID BELTED
Type	TL
Tyre Size	18 X 8.50 - 8
LI/SS FREE ROLLING	85 A8

Dimensions International Standard

Ply Rating	6
Section Width (mm)	225
Overall Diameter (mm)	460
Static Loaded Radius (mm)	217
Rolling Circumference (mm)	1390
Rim Rec	7.00 I - 55 ; I - 70 ; I - 90
ECE	E11-106R-006268

Load capacity (Kg)

km/h / bar	3.00
10 FR	720
25 FR	615
30 FR	575
40 FR	515

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/03/2025 06:43

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..