

## RIB 774 (A) - Technical Specifications



### Description

RIB 774 (A) is a low-section implement tire offering high load capacity and a long tire life-cycle. It is suitable for hay harvesting and transport applications with balers and trailers.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Baler • Hay Harvester • Trailer

Version	STANDARD
Type	TL
Tyre Size	200/60 - 14.5
LI/SS FREE ROLLING	113 A8

## Dimensions US Standard

Usa code	94010998
Ply Rating	14
Section Width (inch)	8.3
Overall Diameter (inch)	24
Static Loaded Radius (inch)	11.3
Rolling Circumference (inch)	74.3
Rim Rec	AG 6.75
ECE	E11-106R-003608

## Load capacity (lbs)

mph / psi	102
5 FR	3550
15 FR	3020
20 FR	2840
25 FR	2540

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 25/03/2025 07:36

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..