

RIB MASTER - Technical Specifications



Description

RIB MASTER is suitable for transport and hay harvesting operations with trailers, balers and implement machinery. This tire offers great load capacity and a long tire life-cycle.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Baler • Implement Machinery • Trailer

Version	STANDARD
Type	TL
Tyre Size	215/75 - 17.5
LI/SS FREE ROLLING	142 A8

Dimensions International Standard

Ply Rating	16
Section Width (mm)	220
Overall Diameter (mm)	775
Static Loaded Radius (mm)	360
Rolling Circumference (mm)	2310
Rim Rec	6.75
ECE	E11-106R-004593

Load capacity (Kg)

	km/h / bar	9.00
	10 FR	3710
	25 FR	3155
	30 FR	2970
	40 FR	2650

Printed on 15/09/2024 02:44

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..