



RIDEMAX FL 615 - Data Sheet



Description

RIDEMAX FL 615 is a radial flotation tire suitable for non-driven wheels of trailers, tankers and spreaders. The steel belted structure offers high puncture resistant with increased durability and high load capacity. RIDEMAX FL 615 provides low rolling resistance on road with outstanding self-cleaning properties on the field. The rounded shoulder and wide footprint area ensure soil protection.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Spreader • Tanker • Trailer

SIZE	Version	LI/SS	LI/SS DRIVE WHEEL	LI/SS FREE ROLLING	RIM REC	RIM ALT	SW	OD	SLR	RC	SRI	Type	ECE
800/65 R 32	STEEL BELTED	185 D	185 D	185 D	DW 27 B		830	1853	834	5624	875	TL	E11-106R-007528
VF800/65 R 32	STEEL BELTED	190 D	190 D	190 D	DW 27 B		830	1853	811	5610	875	TL	E11-106R-0010408

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 26/03/2025 15:12

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..