

AGRIMAX PROHARVEST - Data Sheet



Description

AGRIMAX PROHARVEST is BKT's response to the current market needs in terms of combines and harvesting machines. The advanced VF (Very High Flexion) technology allows AGRIMAX PROHARVEST to carry 40% more load compared to standard tires with the same tire pressure minimizing soil compaction. Moreover, the three layers of steel belts combined with the cut and chip resistant compound ensure excellent puncture resistance, even on case of stubbles or crops leftovers on the field. The structure of the tire with a reinforced bead and a strong polyester carcass is synonym of durability and stability of the tire even during heavy duty operation. The tire casing, engineered to guarantee high load capacity, combined with the CFO (Cyclic Field Operation) technology allows AGRIMAX PROHARVEST to handle temporary overloads during operations like harvesting, reducing stress and wear on the tire. Once the load is reduced, the tire returns to its standard operating condition, thus extending its service life and improving operational efficiency. The open shoulder design improves traction on rough and wet terrain while facilitating the ejection of mud and debris, ensuring smooth transitions from field to road and enhancing safety. On the field and on the road AGRIMAX PROHARVEST can reach up to 65km/h making your transit operation easier and faster thus improving overall productivity.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Harvester

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
VF1000/55 R 32 CFO	STEEL BELTED	94076512	197 D	36.00 VA (multi-piece)		39.6	74.8	33.1	224.5	TL	E11-106R-0010574
VF800/70 R 32 CFO	STEEL BELTED	94512263	187 D	DW 28 B		31.7	76.1	33.3	229	TL	E11-106R-0010664

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/23/2025 3:42 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..