

AGRIMAX RT 657 - Technical Specifications



Description

AGRIMAX RT 657 is the ideal tire for on-the-road usage and soil tillage; some sizes are also suitable for vineyard harvesting. This tire guarantees excellent driving comfort as well as significant fuel savings. It has a high load capacity also at high speed levels. AGRIMAX RT 657 is the best choice for those who need a versatile and reliable tire, with no compromise on performance.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	600/65 R 30
LI/SS	155 D/158 A8

Dimensions International Standard

Section Width (mm)	611
Overall Diameter (mm)	1542
Static Loaded Radius (mm)	697
Rolling Circumference (mm)	4609
SRI (mm)	725
Rim Rec	DW 20 B
Rim Alt	W 18 L
ECE	E4-106R-001825
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6	2.0	2.4
65	1860	2170	2445	2715	2985	3220	3565	3875
50	1955	2280	2565	2850	3135	3380	3745	4070
40	2040	2380	2680	2975	3275	3530	3910	4250
30	2145	2500	2810	3125	3435	3705	4105	4460
10 LT	2495	2910	3275	3640	4005	4315	4780	5195
10 HT	2145	2500	2810	3125	3435	3705	4105	4460

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 8:29 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..