

AGRIMAX RT 765M - Technical Specifications



Description

AGRIMAX RT 765M, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

US Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	710/70 R 42
LI/SS	173D/176A8

Dimensions US Standard

Usa code	94066452
Section Width (inch)	28.2
Overall Diameter (inch)	81.1
Static Loaded Radius (inch)	36.3
Rolling Circumference (inch)	243.1
Rim Rec	DW 23 B
Rim Alt	DW 25 B
ECE	E11-106R-006018
TRA Code	R1W

Load capacity (lbs)

mph / psi	9	12	15	17	20	23	29	35
40	6730	7740	8880	10030	11180	12320	13470	14330
30	7080	8130	9340	10540	11740	12940	14150	15050
25	7390	8480	9730	10990	12250	13500	14760	15700
15	7750	8910	10220	11540	12860	14170	15500	16480
5 LT	9030	10370	11920	13450	14980	16520	18050	19200
5 HT	7750	8910	10220	11540	12860	14170	15500	16480

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 2:14 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..