

AGRIMAX RT 765 - Technical Specifications



Description

AGRIMAX RT 765, a BKT 70 series tire, is suitable for cutting-edge tractors for several heavy-duty applications such as soil tillage, field and road transport, vineyard harvesting, and spraying. A wide contact patch ensures the best possible traction and comfort on all surfaces at any time. This tire provides great self-cleaning properties and reduced soil compaction. Two sizes are available with steel-belted technology.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Sprayer • Tractor • Vineyard Harvester

Version	STANDARD
Type	TL
Tyre Size	480/70 R 38
LI/SS	145 D

Dimensions International Standard

Section Width (mm)	479
Overall Diameter (mm)	1681
Static Loaded Radius (mm)	764
Rolling Circumference (mm)	5055
SRI (mm)	800
Rim Rec	W 15 L
Rim Alt	W 14 L ; W 16 L
ECE	E11-106R-005832
TRA Code	R1W

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
65	1595	1860	2120	2380	2640	2900
50	1675	1950	2225	2500	2775	3045
40	1750	2040	2325	2610	2895	3180
30	1835	2135	2435	2735	3035	3335
10 LT	2140	2490	2840	3190	3540	3890
10 HT	1935	2135	2435	2735	3035	3335

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 8:59 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..