

AGRIMAX TURF RT 333 - Technical Specifications



Description

AGRIMAX TURF RT 333 (R-3+) is a radial tire designed for small tractors in gardening, vineyards and orchards applications. Its rounded shoulder design provides low soil compaction and makes it extremely delicate on the ground. Its unique extra-deep tread (R-3+) and the special design with directional blocks stand for excellent traction both in the field and on the road, and an extended tire life cycle. AGRIMAX TURF RT 333 (R-3+) ensures great selfcleaning properties and thanks to its low rolling resistance, allows for significant fuel saving.

UM

International Standard

Construction



₩ RADIAL

Machinery

Agriculture: Orchard Harvester • Small Tractor • Vineyard Harvester

Version	STANDARD
Туре	TL
Tyre Size	340/85 R 28
LI/SS	127 A8 / 127 B

Dimensions International Standard

Section Width (mm)	370
Overall Diameter (mm)	1289
Static Loaded Radius (mm)	585
Rolling Circumference (mm)	3874
SRI (mm)	625
Rim Rec	W 12
Rim Alt	W11;DW11;DW12
ECE	E11-106R-0010343

Load capacity (Kg)

km/h / bar	0.6	0.8	1.0	1.2	1.4	1.6
50	965	1120	1280	1435	1595	1750
40	965	1120	1280	1435	1595	1750
30	1035	1200	1370	1540	1710	1875
10 LT	1290	1505	1715	1925	2135	2345
10 HT	1035	1200	1370	1540	1710	1875

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 4:48 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..