

AT 171 - Technical Specifications



Description

AT 171 has been specifically designed for mud bogger tractors. The special directional and extra-deep tread design provides excellent traction on wet and muddy surfaces.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: ATV • Mud Bogger Tractor

Version	STANDARD
Type	TL
Tyre Size	AT 33 X 9 - 20
LI/SS	85 A8 / 61 F

Dimensions International Standard

Ply Rating	6
Section Width (mm)	205
Overall Diameter (mm)	838
Static Loaded Radius (mm)	387
Rolling Circumference (mm)	2616
Rim Rec	W 7
Rim Alt	W 6
TRA Code	R1W+

Load capacity (Kg)

km/h / bar	1.40	1.00
40 MUD BOGGING	515	-
80 MUD BOGGING	257	-
40 CASUAL TRANSPORT	-	425
80 CASUAL TRANSPORT	-	218

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 9:51 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..