

# **BK 627 - Technical Specifications**



## **Description**

BK 627 is a block pattern tire suitable for transport and soil tillage operations with trailers and implement machinery. It is mainly field oriented and ideal for heavy-duty service.

#### **UM**

**US Standard** 

#### Construction



## Machinery

Agriculture: Implement Machinery • Tractor • Trailer

Version	STANDARD
Туре	ТТ
Tyre Size	7.50 - 16
LI/SS	121 A8

### **Dimensions US Standard**

Usa code	94041183
Ply Rating	12
Section Width (inch)	8.7
Overall Diameter (inch)	31.9
Static Loaded Radius (inch)	14.4
Rolling Circumference (inch)	98.2
Rim Rec	6.0
ECE	E11-106R-004256

# Load capacity (lbs)

mph / psi	74
25	3200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 5/1/2025 10:22 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..