

BK 826 - Technical Specifications



Description

The BK 826 tire is expertly engineered for trailers in haulage applications, delivering unmatched durability and performance. The 'Harvester Special' version is tailored specifically for harvesting, ensuring optimal reliability in the field. This bias tire boasts a reinforced carcass, offering exceptional load capacity to meet the demands of heavy-duty tasks. Additionally, the BK 826 is available in an "Industrial" variant, designed with superior cut and chip resistance, making it an ideal choice for backhoe loaders in challenging conditions.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Harvester • Trailer

Industrial: Backhoe Loader • Trailer

Version	STANDARD
Type	TT
Tyre Size	9.00 - 16

Dimensions International Standard

Ply Rating	16
Section Width (mm)	265
Overall Diameter (mm)	925
Rim Rec	6.50 H
Rim Alt	6.00 G
ECE	E11-106R-004613

Load capacity (Kg)

km/h / bar	7.25
30	2300

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/3/2025 12:20 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..