

BK-LOADER 53 - Data Sheet



Description

BK-LOADER 53 is an aramid-belted tire designed for loaders in industrial applications. The unique tread design provides best lateral stability in addition to extended tread wear and extraordinary resistance against cuts and punctures thanks to the extra deep tread. BK-LOADER 53 features outstanding self-cleaning properties as well as excellent grip and traction on both wet and dry surfaces. This tire is particularly suitable for recycling operations.

UM

US Standard

Construction



RADIAL

Machinery

Industrial: Loader

SIZE	Version	USACode	LI/SS	RIM REC	RIM ALT	SW	OD	SLR	RC	Type
365/70 R 18	ARAMID BELTED	94074143	146A2/142A4	11		14.2	39	18	118.8	TL
405/70 R 18	ARAMID BELTED	94069705	153A2/149A4	13	14 ; 13 SDC; 12 ;12 SDC	16	41.1	0	0	TL
405/70 R 20	ARAMID BELTED	94054428	155A2/151A4	13	14 ; 13 SDC; 12 ;12 SDC	16	43.2	20.1	131.5	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 9:17 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..