

## COMMANDER (R) - Technical Specifications



### Description

COMMANDER (R) is an agricultural tire featuring a deep tread with strong lug bases for a longer tire life-cycle. The special dual-angle lug design provides excellent traction in the fields and top self-cleaning properties. The strong casing is made of a cut-and-chip-resistant compound providing better puncture resistance together with high load capacity. COMMANDER (R) is the perfect tire for soil tillage, haulage and harvesting operations.

### UM

US Standard

### Construction

 BIAS

### Machinery

Agriculture: Harvester • Tractor

|           |           |
|-----------|-----------|
| Version   | STANDARD  |
| Type      | TT        |
| Tyre Size | 18.4 - 30 |
| LI/SS     | 151 A8    |

Dimensions US Standard

|                              |                 |
|------------------------------|-----------------|
| Usa code                     | 94052752        |
| Ply Rating                   | 18              |
| TMPH                         | 1               |
| Section Width (inch)         | 18.6            |
| Overall Diameter (inch)      | 61.6            |
| Static Loaded Radius (inch)  | 28.9            |
| Rolling Circumference (inch) | 190.3           |
| Rim Rec                      | W 16 L          |
| ECE                          | E11-106R-004368 |
| TRA Code                     | R1              |

Load capacity (lbs)

|           |      |
|-----------|------|
| mph / psi | 46   |
| 25        | 8545 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 2:46 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..