

# **CONTAINER KING - Data Sheet**



### **Description**

CONTAINER KING has been designed for reach stackers in intermodal transport and logistics applications. This extraordinary tire is made of a highly wear-and-tear-resistant tread compound which minimizes tread cracks. CONTAINER KING ensures an extended tire life-cycle plus exceptional stability in lift mode.

#### UM

International Standard

#### Construction



## Machinery

Industrial: Reach Stacker

SIZE	Version	TRA Code	PR	RIM REC	RIM ALT	ow	OD	SLR	RC	Туре
12.00 - 24	INDUSTRIAL	IND4	24	8.5	8.0	330	1285			TT
18.00 - 25	INDUSTRIAL	IND4	40	13.00/2.5	15.00/2.5	528	1675	765	4955	TL
18.00 - 33	INDUSTRIAL	IND4	40	13.00/2.5		510	1895	852	5820	TL

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

#### Printed on 5/2/2025 12:58 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..