

EARTHMAX SR 22 - Data Sheet



Description

EARTHMAX SR 22 (G-2/L-2) is an **All Steel** radial tire specially designed for motor graders and loaders operating in extreme winter conditions on ice or snow. Operators will appreciate both excellent traction and stability provided by the large and non-directional tread design.

UM

International Standard

Construction



RADIAL

Machinery

Industrial: Dozer • Grader • Loader

OTR: Dozer • Grader • Loader

SIZE	Version	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth
14.00 R 24	CUT RESISTANT COMPOUND	G2/L2	*	153 A8/175 A2	8.00 TG	9.00 GR , 10.00 VA	366	1370	625	4141	TL	25
15.5 R 25	CUT RESISTANT COMPOUND	G2/L2	*	146 A8/169 A2	12.00/1.3		385	1275	557	3841	TL	28
17.5 R 25	CUT RESISTANT COMPOUND	G2/L2	*	153 A8/176 A2	14.00/1.5		452	1350	590	3950	TL	28
17.5 R 25	CUT RESISTANT COMPOUND	E2/L2	**	167 B/182 A2	14.00/1.5		452	1350	590	3950	TL	28
20.5 R 25	CUT RESISTANT COMPOUND	G2/L2	*	161 A8/186 A2	17.00/2.0	17.00/1.7	525	1490	640	4315	TL	32
20.5 R 25	CUT RESISTANT COMPOUND	E2/L2	**	177 B/193 A2	17.00/2.0	17.00/1.7	525	1490	640	4315	TL	32
23.5 R 25	CUT RESISTANT COMPOUND	G2/L2	*	170 A8/195 A2	19.50/2.5		610	1614	709	4863	TL	34
23.5 R 25	CUT RESISTANT COMPOUND	E2/L2	**	185 B/201 A2	19.50/2.5		610	1614	709	4863	TL	34

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 4:47 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..