

EARTHMAX SR 402 - Data Sheet



Description

EARTHMAX SR 402 (E-4) is an All Steel radial tire specifically engineered for long-haul dump trucks in mines and quarries. The unique tread design ensures reduced heat buildup and provides excellent traction and stability on all types of terrains and tracks where particular equipment control is a main requirement. The symmetrical, E-4-deep rock tread ensures easy fitment as well as excellent selfcleaning properties even in muddy conditions. The All Steel casing along with the specifically developed tread compound provide excellent wear and extraordinary resistance against cuts and punctures in addition to high load capacity and great durability. As a result, EARTHMAX SR 402 (E-4) reduces machinery downtime and is particularly suitable for long hauls even at full load.

UM

US Standard

Construction



₩ RADIAL

Machinery

OTR: Rigid Dumper • Rigid Dump Truck

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	ow	OD	SLR	RC	Туре	Tread Depth	TMPH
14.00 R 25	CUT RESISTANT COMPOUND	94514465	E4	***	171 B	10.00/2.0		14.8	54.5	25.4	167.8	TL	44	81
16.00 R 25	CUT RESISTANT COMPOUND	94513024	E4	***	183 B	11.25/2.0		17.7	59.8	27.3	182.7	TL	55	90
16.00 R 25	STANDARD COMPOUND	94513000	E4	***	183 B	11.25/2.0		17.7	59.8	27.3	182.7	TL	55	108

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 10:07 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..