

## EARTHMAX SR 45 H2 - Data Sheet



### Description

EARTHMAX SR 45 H2 is an All Steel radial tire specifically designed for rigid haul trucks. The E-4 tread depth and the unique tread pattern ensure excellent wear minimizing vibration and noise. EARTHMAX SR 45 H2 is ideal for all operations requiring traction and stability. The All Steel casing provides excellent resistance to snags and punctures and a long service life. Available in standard, heat-resistant and cut-resistant compounds.

### UM

US Standard

### Construction



RADIAL

### Machinery

OTR: Rigid Dump Truck

SIZE	Version	USACode	TRA Code	Star R	LI/SS	RIM REC	RIM ALT	OW	OD	SLR	RC	Type	Tread Depth	TMPH
24.00 R 35	CUT RESISTANT COMPOUND	94063802	E4	***	212 B	17.00/3.5	---	26	85.8	38.5	259.7	TL	88	228
24.00 R 35	CUT RESISTANT COMPOUND	94060221	E4	**	209 B	17.00/3.5	--	26	85.8	38.5	259.7	TL	88	228
24.00 R 35	HEAT RESISTANT COMPOUND	94063826	E4	***	212 B	17.00/3.5	---	26	85.8	38.5	259.7	TL	88	298
24.00 R 35	HEAT RESISTANT COMPOUND	94060764	E4	**	209 B	17.00/3.5		26	85.8	38.5	259.7	TL	88	298
24.00 R 35	STANDARD COMPOUND	94063819	E4	***	212 B	17.00/3.5	---	26	85.8	38.5	259.7	TL	88	267
24.00 R 35	STANDARD COMPOUND	94059720	E4	**	209 B	17.00/3.5	--	26	85.8	38.5	259.7	TL	88	267

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/23/2025 3:24 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..