

## EM 937 (E3) - Data Sheet



### Description

EM 937 (E-3) has been specially designed for rigid dumpers in surface mining applications. It features excellent durability and provides high cut and chip resistance. EM 937 (E-3) is particularly suitable for heavy duty service.

### UM

International Standard

### Construction

 BIAS

### Machinery

OTR: Rigid Dump Truck

| SIZE       | Version  | TRA Code | PR | RIM REC   | RIM ALT | OW  | OD   | SLR | RC   | Type | Tread Depth |
|------------|----------|----------|----|-----------|---------|-----|------|-----|------|------|-------------|
| 14.00 - 25 | STANDARD | E3/L3    | 28 | 10.00/1.5 |         | 375 | 1368 | 620 | 4105 | TT   | 26          |
| 14.00 - 25 | STANDARD | E3/L3    | 28 | 10.00/1.5 |         | 375 | 1368 | 620 | 4105 | TL   | 26          |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 4/30/2025 11:54 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..