

## FL 630 SUPER - Technical Specifications



### Description

FL 630 SUPER is a flotation tire suitable for field and road applications with trailers, tankers and spreaders. Its resistant structure provides excellent traction and perfect grip even in bends and when maneuvering, while a reinforced bead and steel belts ensure enhanced durability.

### UM

International Standard

### Construction



RADIAL

### Machinery

Agriculture: Spreader • Tanker • Trailer

|           |               |
|-----------|---------------|
| Version   | STANDARD      |
| Type      | TL            |
| Tyre Size | 560/60 R 22.5 |
| LI/SS     | 161 D         |

# Dimensions International Standard

|                            |                |
|----------------------------|----------------|
| Section Width (mm)         | 543            |
| Overall Diameter (mm)      | 1244           |
| Static Loaded Radius (mm)  | 549            |
| Rolling Circumference (mm) | 3785           |
| SRI (mm)                   | 600            |
| Rim Rec                    | AG 16.00       |
| Rim Alt                    | 17.00 ; 20.00  |
| ECE                        | E4-106R-000794 |

## Load capacity (Kg)

| km/h / bar | 0.8  | 1.0  | 1.2  | 1.6  | 2.0  | 2.4  | 2.8  | 3.2  | 3.6  | 4.0  |
|------------|------|------|------|------|------|------|------|------|------|------|
| 70         | 1360 | 1575 | 1785 | 2125 | 2510 | 2870 | 3190 | 3570 | 3910 | 4250 |
| 65         | 1480 | 1715 | 1945 | 2315 | 2730 | 3125 | 3470 | 3885 | 4255 | 4625 |
| 50         | 1795 | 2075 | 2355 | 2800 | 3305 | 3780 | 4200 | 4705 | 5155 | 5600 |
| 40         | 2015 | 2330 | 2645 | 3145 | 3715 | 4250 | 4720 | 5285 | 5790 | 6290 |
| 25         | 2340 | 2710 | 3075 | 3655 | 4315 | 4935 | 5485 | 6145 | 6730 | 7310 |
| 10         | 2665 | 3085 | 3500 | 4165 | 5915 | 5620 | 6245 | 6995 | 7660 | 8325 |

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/6/2025 10:31 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..