

LG 307 - Data Sheet



Description

LG 307 is a lawn and garden tire suitable for mowers. The specific tread pattern makes the tire gentle on the ground to prevent turf damages, easing handling at the same time.

UM

International Standard

Construction

 BIAS

Machinery

Agriculture: Mower

SIZE	Version	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
20 X 10.00 - 8	STANDARD	4	8.00 I - 55 ; I - 70 ; I - 90	7.00 I - 55 ; I - 70 ; I - 90	255	495	215	1435	TL	E11-106R-005200
20 X 10.00 - 8	STANDARD	6	8.00 I - 55 ; I - 70 ; I - 90	7.00 I - 55 ; I - 70 ; I - 90	255	495	215	1435	TL	E11-106R-003462
20 X 12.00 - 10	STANDARD	4	8.5 I - 55 ; I - 70 ; I - 90		285	500	221	1435	TL	E11-106R-003463

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 10:11 PM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..