MP 600 - Data Sheet

Description

MP 600 is an agro-industrial tire, suitable for municipality/maintenance operations with telehandlers and implement machinery, providing a comfortable driving experience. This tire provides good traction and excellent self-cleaning properties along with an extended product life-cycle.

UM

International Standard

Construction

❖ BIAS

Machinery

Agriculture: Implement Machinery • Telehandler
Industrial: Telehandler • Universal Vehicle

SIZE	Version	LI/SS DRIVE WHEEL	PR	RIM REC	RIM ALT	SW	OD	SLR	RC	Type	ECE
10.5 - 18	STANDARD		10	9	9 SDC	272	920	420	2740	TL	E11-106R-003581
12.5 - 18	STANDARD		10	11	12 SDC	308	990	450	2950	TL	
12.5 - 18	STANDARD		12	11	12 SDC	308	990	450	2950	TL	
400/70 - 20 (16.0/70 - 20)	STANDARD		14	13 SDC	12	405	1085	0	0	TL	
400/70 - 24 (16.0/70 - 24)	SPECIAL		14	13 SDC	12	405	1185	545	3530	TL	
400/70 - 24 (16.0/70 - 24)	STANDARD		14	13 SDC	12	405	1185	545	3530	TL	E11-106R-003640
400/70 - 24 (16.0/70 - 24)	STANDARD		10	13 SDC	12	405	1185	545	3530	TL	
400/70 - 24 (16.0/70 - 24)	STANDARD	158 A8	18	13 SDC	12	405	1185	545	3530	TL	E11-106R-003641

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 7:42 AM