



MULTI RIB - Data Sheet



Description

MULTI RIB is an agro-industrial tire for soil tillage and transport applications with 2WD tractors and implement machinery. It offers excellent handling throughout its long product life-cycle. Several versions are available for every need: an "aramid belted" version with improved puncture resistance, while the "HD" is made of a special cut-and-chip resistance compound.

UM

US Standard

Construction

 BIAS

Machinery

Agriculture: 2WD Tractor • Implement Machinery

SIZE	Version	USACode	PR	RIM REC	RIM ALT	SW	OD	Type	ECE
11.00 - 16	ARAMID BELTED HD	94052516	12	W10 L	W 8 ; W 8 L	12.4	36.6	TL	E11-106R-005377
11.00 - 16	HD	94061624	12	W10 L	W 8 ; W 8 L	12.4	36.6	TL	
11.00 - 16	STANDARD	94006199	12	W10 L	W 8 ; W 8 L	12.4	36.6	TL	E11-106R-004649

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/2/2025 12:58 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..