

RIDEMAX IT 696 - Technical Specifications



Description

RIDEMAX IT 696 has a unique tread design and a wide footprint that provides excellent grip for road applications, even in winter conditions. The tire is best suitable for transport and municipality/maintenance applications thanks to its high-speed feature and strong casing. The tread design has been specifically developed for heavy-duty services and ensures a low rolling resistance that provides fuel economy plus great stability.

UM

International Standard

Construction

 RADIAL

Machinery

Agriculture: Tractor

Version	STANDARD
Type	TL
Tyre Size	240/70 R 16 IND
LI/SS	107A8/107B

Dimensions International Standard

Section Width (mm)	244
Overall Diameter (mm)	742
Static Loaded Radius (mm)	343
Rolling Circumference (mm)	2226
SRI (mm)	350
Rim Rec	W8
Rim Alt	W9
ECE	E11-106R-006942

Load capacity (Kg)

km/h / bar	1.2	1.6	2.0	2.4	2.8
50	545	675	730	860	975
40	545	675	730	860	975
30	585	725	785	985	1045
20	675	835	900	1135	1200

Rolling Circumference & SLR values are at rated Load and inflation pressure. These values may vary at different Load and pressure condition.

Printed on 5/1/2025 11:39 AM

All product data contained in this publication are for information purposes only and may be modified at any time without prior notice. Balkrishna Industries Ltd. or any of its subsidiary companies does not undertake any responsibility or liability for undetected errors and/or misprints. All rights reserved. The materials and contents of this publication and the website are the exclusive property of Balkrishna Industries Ltd. and are protected by industrial and/or intellectual property laws. The user is not permitted to copy, reproduce, transfer, upload, make use of, publish or spread any contents, in whole or in part, on paper format, electronic format or otherwise without prior written consent by Balkrishna Industries Ltd..